

CNSQuery_AddField

Name	CNSQuery_AddField
Description	<p>This function Adds a new Field to an existing Table. The first parameter is the Name of a Table Occurrence of the Table to Add the new Field to. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the current Table and Add the Field to that Table. The second parameter is the name for the new Field. The third parameter is the Type of Field to Add and can be any one of the following values: "Text", "Number", "Date", "Time", "Timestamp", or "Container". If you do not specify the Field Type, CNS Query will create a "Text" Field. If you are using FileMaker Pro 8.5 or above, you can use the fourth parameter to specify if the new Field should be a Global Field. By default, CNS Query will check to make sure the Table Name you specify exists before attempting to Add the new Field. If you already know for sure that the Table exists, you can pass True as the fifth parameter.</p> <p>Note: In FileMaker Pro 8.5 and above, you must insert a "Pause" Script Step after using this function in order for the new Field to be Added.</p>
Return Type	Text
Format	CNSQuery_AddField (TOName ; FieldName ; FieldType ; AsGlobal ; SkipTONameCheck)
Required Parameters	<p>TOName The Name of a Table Occurrence for the Table to receive the new Field. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database FileName (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldName The Name of the new Field.</p>
Optional Parameters	<p>FieldType The Type of Field to Add. Specify "Text", "Number", "Date", "Time", "Timestamp", or "Container". CNS Query uses "Text" as the default.</p> <p>AsGlobal If True, the plug-in will Add a Field with Global storage instead of a normal Field. This parameter is only available in FileMaker Pro 8.5 and above.</p> <p>SkipTONameCheck If True, the plug-in will not check to make sure the TO Name you specified actually exists before attempting to Add the Field.</p>

Related Items	CNSQuery_FieldExists CNSQuery_GetFieldIDs CNSQuery_GetFieldNames CNSQuery_GetFieldTypes CNSQuery_GetFieldValueByFind CNSQuery_GetFieldValueByID CNSQuery_RemoveField CNSQuery_SetFieldValueByFind CNSQuery_SetFieldValueByID
Examples	<p>Example 1 Adds a new Text Field named "MyField" to the "MyTable" Table.</p> <pre>CNSQuery_AddField("MyTable" ; "MyField")</pre> <hr/> <p>Example 2 Adds a new Global Number Field named "gNum" to the current Table. (This would only work on FileMaker Pro 8.5 and above.)</p> <pre>CNSQuery_AddField("" ; "gNum" ; "Number" ; True)</pre> <hr/> <p>Example 3 In FileMaker Pro 11 and above, use this form to add a field to a Table Occurrence in a separate, open Database file.</p> <pre>CNSQuery_AddField("AnotherFile.MyTable" ; "MyField")</pre>

CNSQuery_AddRecord

Name	CNSQuery_AddRecord
Description	<p>This function Adds a new Record to an existing Table. The first parameter is the Name of a Table Occurrence of the Table to receive the new Record. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the current Table and Add the Record to that Table. The second parameter is a return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the Field Values for the new Record. If a Field Value needs a return in it, you can use "<CR>" to indicate the return. By default, CNS Query will check to make sure the Table Name and all the Field Names you specify exist before attempting to Add the new Record. If you already know for sure that the Table Name and the Field Names exist, you can pass True as the third and fourth parameters.</p>
Return Type	Text
Format	CNSQuery_AddRecord (TOName ; FieldValues ; SkipTONameCheck ; SkipFieldNameChecks)
Required Parameters	<p>TOName The Name of a Table Occurrence for the Table to receive the new Record. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldValues A return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the Field Values for the new Record. Use "" to indicate a return or new line in a Field Value.</p>
Optional Parameters	<p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specified actually exists before attempting to Add the Record.</p> <p>SkipFieldNameChecks If True, CNS Query will not check to make sure all the Field Names in the FieldValues parameter actually exist before attempting to Add the Record.</p>
Related Items	CNSQuery_FindRecords CNSQuery_RemoveRecordByFind CNSQuery_RemoveRecordByID CNSQuery_UpdateRecordByFind CNSQuery_UpdateRecordByID

Examples

Example 1

Adds a new Record to the "MyTable" Table setting the "MyField" and "AnotherField" Fields.

```
CNSQuery_AddRecord( "MyTable" ; "MyField=Some  
value¶AnotherField=Some other value" )
```

Example 2

Adds a new Record to the current Table setting the "MyField" field with a multi-line value.

```
CNSQuery_AddRecord( "" ;  
"MyField=A<CR>value<CR>with<CR>multiple<CR>lines" )
```

Example 3

In FileMaker Pro 11 and above, use this form to add a new Record to a Table Occurrence in a separate, open Database file.

```
CNSQuery_AddRecord( "AnotherFile.MyTable" ; "MyField=Some  
value" )
```

CNSQuery_AddTable	
Name	CNSQuery_AddTable
Description	<p>This function Adds a new Table to the current Database File. The first parameter is the Name of the new Table, which must be unique for the current Database File. The second parameter is a return- or paragraph mark-separate list of "FieldName=FieldType" pairs used to describe the Fields that should be Added to the new Table. Valid Field Types are "Text", "Number", "Date", "Time", "Timestamp", and "Container". If you are using FileMaker Pro 8.5 or above, you can also specify the following Global Field Types: "GlobalText", "GlobalNumber", "GlobalDate", "GlobalTime", "GlobalTimestamp", and "GlobalContainer".</p> <p>Note: In FileMaker Pro 8.5 and above, you must insert a "Pause" Script Step after using this function in order for the new Table to be Added.</p>
Return Type	Text
Format	CNSQuery_AddTable (TableName ; FieldDefinitions)
Required Parameters	<p>TableName The Name of the Table to Add. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TableName".</p> <p>FieldDefinitions A return- or paragraph mark-separated list of "FieldName=FieldType" pairs describing the Field Names for the new Table. Use "Text", "Number", "Date", "Time", "Timestamp", "Container", "GlobalText", "GlobalNumber", "GlobalDate", "GlobalTime", "GlobalTimestamp", and "GlobalContainer" as the Field Types.</p>
Related Items	<p>CNSQuery_GetTOIDs CNSQuery_GetTONames CNSQuery_RemoveTable CNSQuery_TOExists CNSQuery_GetBaseTableNames</p>
Examples	<p>Example 1 Adds a new Table to the current Database File containing two fields named "AField" and "BField" which have the Field Types Text and Number respectively.</p> <pre>CNSQuery_AddTable("MyNewTable" ; "AField=Text¶BField=Number"</pre>

)

Example 2

In FileMaker Pro 11 and above, use this form to add a new Table in a separate, open Database file.

```
CNSQuery_AddTable( "AnotherFile.MyNewTable" ; "AField=Text" )
```

CNSQuery_EscapeQuotes

Name	CNSQuery_EscapeQuotes
Description	This is a utility function that takes raw Text and conforms it to what the ExecuteSQL function needs in order to function correctly. It turns any Backward Slashes (\) into a double-Backward Slash (\\) and turns any Single Quotes (') into Backward Slash-Single Quote (\').
Return Type	Text
Format	CNSQuery_EscapeQuotes (Text)
Required Parameters	Text The Text to conform to what ExecuteSQL needs.
Related Items	CNSQuery_ExecuteSQL CNSQuery_ExecuteSQLEx
Example	Example 1 Returns "I can\'t seem to find the backslash (\\) on my keyboard." CNSQuery_EscapeQuotes("I can't seem to find the backslash (\\) on my keyboard.")

CNSQuery_ExecuteSQL

Name	CNSQuery_ExecuteSQL
Description	This function allows you to use SQL statements to run queries against the current Database File. If the Query you are using will be returning Field values and multiple Records, you can optionally define the Separators that should be placed between the Fields and Records using the last two parameters. By default, CNS Query will use a comma between multiple Fields and a return between multiple Records. The Field and Record Separators you specify are not limited to a single character.
Return Type	Text
Format	CNSQuery_ExecuteSQL (SQL ; FieldSeparator ; RecordSeparator)
Required Parameters	SQL The SQL statement to evaluate against the current Database File.
Optional Parameters	FieldSeparator The Separator to use between multiple Fields when doing an SQL Select. By default, Fields will be separated with a comma. RecordSeparator The Separator to use between multiple Records when doing an SQL Select. By default, Records will be separated with a return.
Related Items	CNSQuery_EscapeQuotes CNSQuery_ExecuteSQLEx CNSQuery_GetAsSQLDate CNSQuery_GetAsSQLTime CNSQuery_GetAsSQLTimestamp
Examples	Example 1 Returns every field and every record from the "MyTable" Table. <pre>CNSQuery_ExecuteSQL("select * from MyTable")</pre> <hr/> Example 2 Returns something like "<tr><td>Mary</td><td>Jones</td></tr>" for every record in the "MyTable" Table. <pre>CNSQuery_ExecuteSQL("select '<tr><td>' + \"First\\", \"Last\\\" + '</td></tr>' from MyTable" ; "</td><td>")</pre>

CNSQuery_FieldExists

Name	CNSQuery_FieldExists
Description	<p>This function checks for the Existence of a Field in an existing Table. The first parameter is the Name of a Table Occurrence of the Table to look at for the Field. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the current Table to look at for the Field. The second parameter is the Name of the Field to look for. By default, CNS Query will check to make sure the TO Name you specify exists before searching it for the Field. If you already know for sure that the TO exists, you can pass True as the third parameter.</p>
Return Type	Number (1=True, 0=False)
Format	CNSQuery_FieldExists (TOName ; FieldName ; SkipTONameCheck)
Required Parameters	<p>TOName The Name of the Table Occurrence to search. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldName The Name of the Field to search for.</p>
Optional Parameters	<p>SkipTONameCheck If True, the plug-in will not check to make sure the TO Name you specified actually exists before searching it for the Field.</p>
Related Items	<p>CNSQuery_AddField CNSQuery_GetFieldIDs CNSQuery_GetFieldNames CNSQuery_GetFieldTypes CNSQuery_GetFieldValueByFind CNSQuery_GetFieldValueByID CNSQuery_RemoveField CNSQuery_SetFieldByFind CNSQuery_SetFieldByID</p>
Examples	<p>Example 1 Returns 1 when a Field Named "AField" exists in a Table Named "MyTable".</p> <pre>CNSQuery_FieldExists("MyTable" ; "AField")</pre>

Example 2

Returns 0 when a Field Named "DoesntExist" does not exist in the current Table.

```
CNSQuery_FieldExists( "" ; "DoesntExist" )
```

Example 3

In FileMaker Pro 11 and above, use this form to add a check for a field in a Table Occurrence in a separate, open Database file.

```
CNSQuery_FieldExists( "AnotherFile.MyTable" ; "AField" )
```

CNSQuery_FindRecords

Name

CNSQuery_FindRecords

Description

This function does a Find against a Table and returns all matches. The first parameter is the Name of the Table Occurrence to perform the Find in. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the current TO to perform the Find in. The second parameter is a return- or paragraph mark-separated list of "FieldName=FieldValue" pairs that describes the Criteria for Finding the Records you want. See the "Finding What You Want" section below for help in defining your Find Criteria. The FieldNamesToReturn parameter is a return- or paragraph mark-separated list of Fields you want returned in the Result. In other words, if you have 10 fields in your Table, but you are only interested in the values of the "FirstName" and "LastName" fields, you would specify "FirstName&¶LastName" as the FieldNamesToReturn parameter. (Note: You can specify fields in the FindCriteria other than what you want returned in the result.) The fourth parameter is a return- or paragraph mark-separated list of "FieldNames=SortDirection" pairs that define how to Sort the Result. For the Sort Direction you can use "Asc" or "Desc" to sort Ascending or Descending respectively. By default, CNS Query will use a comma between multiple Fields and a return between multiple Records. If you need to use different Separators, you can use the fifth and sixth parameters. The Field and Record Separators are not limited to a single character. By default, CNS Query will check to make sure the TO Name and all the Field Names you specify exist before attempting to perform the Find. If you already know for sure that the TO Name and the Field Names exist, you can pass True as the seventh and eighth parameters. If you want the Find to be Case Sensitive, you can specify True as the ninth parameter. Finally, if you are running FileMaker Pro 11 or above, you can use the tenth parameter to specify that the function store the results internally to be retrieved later using the CNSQuery_GetRecordData function.

Finding What You Want

The FindCriteria parameter in this function and other related functions allows you to define exactly which Records in your Table that you want to work with. Not every Find you want to do is as simple as saying, "This field needs this exact value in it". So, this section explains how to do more complex Finds to get exactly what you want. First, let's say we have a table with the following values in it:

Record	FirstName	LastName	Colors
1	Mary	Jones	Red

			Blue
2	LeAnn	Johnson	Green-Yellow Red
3	Ann	Parsons	Green Orange

Now, the following are different FindCriteria parameters you can use and what CNS Query would return for each:

- "FirstName=Mary" - This would return Record number 1. Specifying a single Value for a Field will return any Record where that Field's Value is exactly what you specified.
- "FirstName=Mary&|Ann" - This would return Record numbers 1 and 3. Specifying multiple Values for a Field will return any Record where that Field's Value is exactly one of those Values. Note that this does not match the value "LeAnn" in the second record.
- "::Contains::FirstName=Ann" - This would return Record numbers 2 and 3. Using the special "::Contains::" keyword before the Field Name tells CNS Query to match the Value anywhere in the Field instead of matching the Field Value exactly.
- "::Begins-With::LastName=J" - This would return Record numbers 1 and 2. Using the special "::Begins-With::" keyword before the Field Name tells CNS Query to find any Record whose Field Value starts with the Value you specify.
- "::Ends-With::FirstName=n" - This would return Record numbers 2 and 3. Using the special "::Ends-With::" keyword before the Field Name tells CNS Query to find any Record whose Field Value ends with the Value you specify.
- "Colors=Blue" - This would not return any Records because none of the Records have the exact value "Blue" for the "Colors" field.
- "::Contains::Colors=Blue&|Green" - This would return Record numbers 1, 2 and 3. Since the "::Contains::" keyword will tell CNS Query to find the Value anywhere in the Field, this will match "Green-Yellow" in the second Record.
- "::Contains-Value::Colors=Blue&|Green" - This would return Record numbers 1 and 3. The special "::Contains-Value::" keyword before the Field Name tells CNS Query to find exact Values in the Field. (A Value is defined here as any Text that is on a line by itself.)

Return Type	Text
Format	CNSQuery_FindRecords (TOname ; FindCriteria ; FieldNamesToReturn ; SortFields ; FieldSeparator ; RecordSeparator ; SkipTOnameCheck ; SkipFieldNameChecks ; CaseSensitive ; UseRecordData)

Required Parameters

TOName

The Name of a Table Occurrence of the Table to perform the Find in. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".

FindCriteria

A return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the Criteria for the Find. See the "Finding What You Want" section above for help in setting up the Find Criteria.

Optional Parameters

FieldNamesToReturn

A return- or paragraph mark-separated list of Field Names that you want returned from the Find. If you do not specify this parameter, all Fields will be returned.

SortFields

A return- or paragraph mark-separated list of "FieldName=SortDirection" pairs describing the Sort order for the returned data. Use "Asc" or "Desc" for the Sort Direction to indicate Ascending or Descending respectively.

FieldSeparator

The Separator to use between multiple Fields. By default, Fields will be separated with a comma.

RecordSeparator

The Separator to use between multiple Records. By default, Records will be separated with a return.

SkipTONameCheck

If True, CNS Query will not check to make sure the TO Name you specified actually exists before performing the Find.

SkipFieldNameChecks

If True, CNS Query will not check to make sure all the Field Names in the various parameters actually exist before performing the Find.

CaseSensitive

If True, CNS Query will preserve the Case in the Field Values of the Find Criteria. (In other words, if CaseSensitive is True, "Green" would not match "green".)

UseRecordData

If True, this function will return a blank response when successful and you can use the CNSQuery_GetRecordData function to retrieve any data. The default is False. (Note: This parameter is only available under FileMaker Pro 11 and above.)

Related Items	CNSQuery_AddRecord CNSQuery_GetFieldValueByFind CNSQuery_RemoveRecordByFind CNSQuery_RemoveRecordByID CNSQuery_SetFieldByFind CNSQuery_SetFieldByID CNSQuery_UpdateRecordByFind CNSQuery_UpdateRecordByID CNSQuery_GetRecordData CNSQuery_GetRecordDataColumnCount CNSQuery_GetRecordDataRowCount
Examples	<p>Example 1 Returns all Records from the "MyTable" Table where the Field "AField" has the value "Some Value".</p> <pre>CNSQuery_FindRecords("MyTable" ; "AField=Some Value")</pre> <hr/> <p>Example 2 Returns all Records from the current Table where the "LastName" Field is set to either Jones or Johnson. The Result will only contain the LastName and FirstName fields (in that order) separated by a comma and a space, and Sorted Descending by Last Name and then First Name.</p> <pre>CNSQuery_FindRecords("" ; "LastName=Jones<CR>Johnson" ; "LastName¶FirstName" ; "LastName=Desc¶FirstName=Desc" ; ", ")</pre> <hr/> <p>Example 3 Returns all Records from the current Table where the word "Green" appears somewhere in the "Colors" Field.</p> <pre>CNSQuery_FindRecords("" ; "::Contains::Colors=Green")</pre> <hr/> <p>Example 4 Returns all Records from the current Table where the "LastName" Field starts with the letter "J".</p> <pre>CNSQuery_FindRecords("" ; "::Begins-With::LastName=J")</pre> <hr/>

Example 5

In FileMaker Pro 11 and above, use this form to Find Records in a Table Occurrence in a separate, open Database file and store the results internally to later be retrieved with CNSQuery_GetRecordData.

```
CNSQuery_FindRecords( "AnotherFile.MyTable" ; "AField=Some  
Value" ; "" ; "" ; "" ; "" ; "" ; "" ; "" ; "" ; True )
```

CNSQuery_GetFieldIDs

Name	CNSQuery_GetFieldIDs
Description	<p>This function returns either the ID of a specific Field or a list of "FieldName=FieldID" pairs for all Fields in a Table. The first parameter is the Name of a Table Occurrence of the Table to return the Field IDs from. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the current Table to return the Field IDs from. If you specify a Field Name in the second parameter, CNS Query will return the Field ID of that specific Field. If you do not specify this parameter, CNS Query will return a list of "FieldName=FieldID" pairs for all the Fields in the Table. By default, CNS Query will check to make sure the TO Name and the Field Name you specify exist before getting the Field IDs. If you already know for sure that the TO Name and the Field Name exist, you can pass True as the third and fourth parameters.</p> <p>Note: In FileMaker Pro 7 through 10, to ensure that you get the Field IDs of all the Fields in your Table, you must make sure that there is not a Layout in your Database with the same name as the TO Name you specify for this function. In FileMaker Pro 11 and above, this is not an issue.</p>
Return Type	Text or Number
Format	CNSQuery_GetFieldIDs (TOName ; FieldName ; SkipTONameCheck ; SkipFieldNameCheck)
Optional Parameters	<p>TOName The Name of a Table Occurrence of the Table that contains the Fields. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldName If you specify this parameter, CNS Query will return the ID of the Field you specify. Otherwise, CNS Query will return all the IDs of all the Fields.</p> <p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specify actually exists.</p> <p>SkipFieldNameCheck If True, CNS Query will not check to make sure the Field Name you specify actually exists.</p>
Related Items	CNSQuery_AddField

CNSQuery_FieldExists
CNSQuery_GetFieldNames
CNSQuery_GetFieldTypes
CNSQuery_GetFieldValueByFind
CNSQuery_GetFieldValueByID
CNSQuery_RemoveField
CNSQuery_SetFieldValueByFind
CNSQuery_SetFieldValueByID

Examples

Example 1

Returns something like:

AField=1

BField=2

```
CNSQuery_GetFieldIDs( "MyTable" )
```

Example 2

Returns 2 if the Field ID for the "BField" Field in the current Table is 2.

```
CNSQuery_GetFieldIDs( "" ; "BField" )
```

Example 3

In FileMaker Pro 11 and above, use this form to get the Field IDs of a Table in a separate, open Database file.

```
CNSQuery_GetFieldIDs( "AnotherFile.MyTable" )
```

CNSQuery_GetFieldNames

Name	CNSQuery_GetFieldNames
Description	<p>This function returns a list of Field Names from a Table. The first parameter is the name of a Table Occurrence of the Table to return the Field Names from. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the current Table to return the Field Names from. By default, CNS Query will check to make sure the TO Name you specify exists before getting the Field Names. If you already know for sure that the TO Name exists, you can pass True as the second parameter.</p> <p>Note: In FileMaker Pro 7.0 to FileMaker Pro 8.0, to ensure that you get the Names of all the Fields in your Table, you must make sure that there is not a Layout in your Database with the same name as the TO Name you specify for this Function. If you are using FileMaker Pro 8.5 or above, this is no longer an issue.</p>
Return Type	Text
Format	CNSQuery_GetFieldNames (TOName ; SkipTONameCheck)
Optional Parameters	<p>TOName The Name of a Table Occurrence of the Table that contains the Fields. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specify actually exists.</p>
Related Items	CNSQuery_AddField CNSQuery_FieldExists CNSQuery_GetFieldIDs CNSQuery_GetFieldTypes CNSQuery_GetFieldValueByFind CNSQuery_GetFieldValueByID CNSQuery_RemoveField CNSQuery_SetFieldValueByFind CNSQuery_SetFieldValueByID
Examples	Example 1

Returns something like:

AField

BField

```
CNSQuery_GetFieldNames( "MyTable" )
```

Example 2

In FileMaker Pro 11 and above, use this form to get the Field Names of a Table in a separate, open Database file.

```
CNSQuery_GetFieldNames( "AnotherFile.MyTable" )
```

CNSQuery_GetFieldTypes

Name	CNSQuery_GetFieldTypes
Description	<p>This function returns either the Field Type of a specific Field or a List of "FieldName=FieldType" pairs for all Fields in a Table. The first parameter is the Name of a Table Occurrence of the Table to return the Field Types from. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout TO to return the Field Types from. If you specify a Field Name in the second parameter, CNS Query will return the Field Type of that specific Field. If you do not specify this parameter, CNS Query will return a list of "FieldName=FieldType" pairs for all the Fields in the Table. By default, CNS Query will check to make sure the TO Name and the Field Name you specify exist before getting the Field Types. If you already know for sure that the TO Name and Field name exist, you can pass True as the third and fourth parameters.</p> <p>Note: In FileMaker Pro 7 through 10, to ensure that you get the Field Types of all the Fields in your Table, you must make sure that there is not a Layout in your Database with the same name as the TO Name you specify for this function. In FileMaker Pro 11 and above, this is no longer an issue.</p>
Return Type	Text
Format	CNSQuery_GetFieldTypes (TOName ; FieldName ; SkipTONameCheck ; SkipFieldNameCheck)
Optional Parameters	<p>TOName The Name of a Table Occurrence of the Table that contains the Fields. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldName If you specify this parameter, CNS Query will return the Field Type of the Field you specify. Otherwise, CNS Query will return all the Field Type of all the Fields.</p> <p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specify actually exists.</p> <p>SkipFieldNameCheck If True, CNS Query will not check to make sure the Field Name you specify actually exists.</p>

Related Items	CNSQuery_AddField CNSQuery_FieldExists CNSQuery_GetFieldNames CNSQuery_GetFieldTypes CNSQuery_GetFieldValueByFind CNSQuery_GetFieldValueByID CNSQuery_RemoveField CNSQuery_SetFieldValueByFind CNSQuery_SetFieldValueByID
Examples	<p>Example 1 Returns something like:
 AField=Text
 BField=Calculation (Number)
 CField=Global Timestamp</p> <pre>CNSQuery_GetFieldTypes("MyTable")</pre> <hr/> <p>Example 2 Returns "Text" if the Field Type for the "AField" Field in the current Table is a Text Field.</p> <pre>CNSQuery_GetFieldTypes("" ; "AField")</pre> <hr/> <p>Example 3 In FileMaker Pro 11 and above, use this form to get the Field Types of a Table in a separate, open Database file.</p> <pre>CNSQuery_GetFieldTypes("AnotherFile.MyTable")</pre>

CNSQuery_GetFieldValueByFind

Name	CNSQuery_GetFieldValueByFind
Description	<p>This function retrieves the Value of a single Field using Find Criteria. The first parameter is the Name of a Table Occurrence of the Table to Get the Field Value from. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout TO to Get the Field Value from. The second parameter is the Name of the Field to retrieve. The third parameter is a return- or paragraph mark-separated list of "FieldName=FieldValue" pairs that describes the Criteria for Finding the Record to Get the Field Value from. See the "Finding What You Want" section in the CNSQuery_FindRecords function for help in defining your Find Criteria. By default, CNS Query will check to make sure the TO Name and all the Field Names you specify exist before attempting to Get the Field Value. If you already know for sure that the TO Name and the Field Names exist, you can pass True as the fourth and fifth parameters. Finally, if you want the Find to be Case Sensitive, you can specify True as the last parameter.</p>
Return Type	Varies
Format	CNSQuery_GetFieldValueByFind (TOName ; FieldName ; FindCriteria ; SkipTONameCheck ; SkipFieldNameChecks ; CaseSensitive)
Required Parameters	<p>TOName The Name of a Table Occurrence of the Table to Get the Field Value from. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldName The Name of the Field to retrieve the Value from.</p> <p>FindCriteria A return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the Criteria for Finding the Record to get the Field Value from. See the "Finding What You Want" section of the CNSQuery_FindRecords function for help in setting up the Find Criteria.</p>
Optional Parameters	<p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specified actually exists before retrieving the Field Value.</p> <p>SkipFieldNameChecks</p>

If True, CNS Query will not check to make sure all the Field Names in the various parameters actually exist before retrieving the Field Value.

CaseSensitive

If True, CNS Query will preserve the Case in the Field Values of the Find Criteria. (In other words, if CaseSensitive is True, "Green" would not match "green".)

Related Items

CNSQuery_AddField
CNSQuery_FieldExists
CNSQuery_GetFieldIDs
CNSQuery_GetFieldNames
CNSQuery_GetFieldTypes
CNSQuery_FindRecords
CNSQuery_GetFieldValueByID
CNSQuery_RemoveField
CNSQuery_SetFieldValueByFind
CNSQuery_SetFieldValueByID

Examples

Example 1

This would retrieve the Value of the "BField" Field from the "MyTable" Table from the Record where the "AField" Field has the Value "some value".

```
CNSQuery_GetFieldValueByFind( "MyTable" ; "BField" ;  
"AField=some value" )
```

Example 2

This would retrieve the Value of the "LastName" Field from the current Table from the Record where the "FirstName" Field has the value "Ann".

```
CNSQuery_GetFieldValueByFind( "" ; "LastName" ;  
"FirstName=Ann" )
```

Example 3

In FileMaker Pro 11 and above, use this form to get the Field Value from a Table Occurrence in a separate, open Database file.

```
CNSQuery_GetFieldValueByFind( "AnotherFile.MyTable" ;  
"BField" ; "AField=some value" )
```

CNSQuery_GetFieldValueByID

Name	CNSQuery_GetFieldValueByID
Description	<p>This function retrieves the Value of a Single Field from a Record with a specific ID. The first parameter is the Name of a Table Occurrence of the Table to Get the Field Value from. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout TO to Get the Field Value from. The second parameter is the Name of the Field to retrieve. The third parameter is the Internal FileMaker Record ID of the Record to retrieve the Field Value from. If you do not specify this parameter, CNS Query will use Get(RecordID) to get the Record ID. By default, CNS Query will check to make sure the TO Name, the Field Name, and the Record ID you specify exist before attempting to Get the Field Value. If you already know for sure that the TO Name, the Field Name, and the Record ID exist, you can pass True as the fourth, fifth, and sixth parameters.</p>
Return Type	Varies
Format	CNSQuery_GetFieldValueByID (TOName ; FieldName ; FMRecID ; SkipTONameCheck ; SkipFieldNameCheck ; SkipFMRecIDCheck)
Required Parameters	<p>TOName The Name of a Table Occurrence for the Table to Get the Field Value from. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldName The Name of the Field to retrieve the Value from.</p>
Optional Parameters	<p>FMRecID The Internal FileMaker Record ID of the Record to Get the Field Value from.</p> <p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specified actually exists before retrieving the Field Value.</p> <p>SkipFieldNameCheck If True, CNS Query will not check to make sure the Field Name you specified actually exists before retrieving the Field Value.</p> <p>SkipFMRecIDCheck If True, CNS Query will not check to make sure the Record ID you specified actually exists before retrieving the Field Value.</p>

Related Items	CNSQuery_AddField CNSQuery_FieldExists CNSQuery_GetFieldIDs CNSQuery_GetFieldNames CNSQuery_GetFieldTypes CNSQuery_GetFieldValueByFind CNSQuery_RemoveField CNSQuery_SetFieldValueByFind CNSQuery_SetFieldValueByID
Examples	<p>Example 1 This would retrieve the Value of the "AField" Field from the "MyTable" Table from the Record with the ID 4.</p> <pre>CNSQuery_GetFieldValueByID("MyTable" ; "AField" ; 4)</pre> <hr/> <p>Example 2 This would retrieve the Value of the "FirstName" Field from the current Table from the current Record.</p> <pre>CNSQuery_GetFieldValueByFind("" ; "FirstName")</pre> <hr/> <p>Example 3 In FileMaker Pro 11 and above, use this form to get the Field Value from a Table Occurrence in a separate, open Database file.</p> <pre>CNSQuery_GetFieldValueByID("AnotherFile.MyTable" ; "AField")</pre>

CNSQuery_GetFMErrorText

Name	CNSQuery_GetFMErrorText
Description	This function returns the Error Text associated with a FileMaker Pro error number.
Return Type	Text
Format	CNSQuery_GetFMErrorText (ErrorNumber)
Required Parameters	ErrorNumber The Error Number of the Error Text you want.
Example	Example 1 Returns "Table is missing (106)". CNSQuery_GetFMErrorText(106)

CNSQuery_GetLayoutFieldNames

Name	CNSQuery_GetLayoutFieldNames
Description	This function returns a list of Field Names from a Layout. The first parameter is the Name of the Layout to return the Field Names from. If you do not specify this parameter, CNS Query will use Get(LayoutName) to get the current Layout to return the Field Names from. By default, CNS Query will check to make sure the Layout Name you specify exists before getting the Field Names. If you already know for sure that the Layout Name exists, you can pass True as the second parameter.
Return Type	Text
Format	CNSQuery_GetLayoutFieldNames (Layout Name ; SkipLayoutNameCheck)
Optional Parameters	<p>Layout Name The Name of the Layout that contains the Fields. You can specify "" here to have CNS Query use the current Layout.</p> <p>SkipLayoutNameCheck If True, CNS Query will not check to make sure the Layout Name you specify actually exists.</p>
Related Items	CNSQuery_GetLayoutIDs CNSQuery_GetLayoutNames CNSQuery_LayoutExists
Example	<p>Example 1 Returns something like:
 AField
 BField
 Related::DField</p> <p>CNSQuery_GetLayoutFieldNames("MyLayout")</p>

CNSQuery_GetLayoutIDs

Name	CNSQuery_GetLayoutIDs
Description	This function returns either the ID of a specific Layout or a list of "LayoutName=LayoutID" pairs for all Layouts in the current Database File. If you specify a Layout Name in the first parameter, CNS Query will return the Layout ID of that specific Layout. If you do not specify this parameter, CNS Query will return a list of "LayoutName=LayoutID" pairs for all the Layouts in the current Database File. By default, CNS Query will check to make sure the Layout Name you specify exists before getting the Layout IDs. If you already know for sure that the Layout name exists, you can pass True as the second parameter.
Return Type	Text or Number
Format	CNSQuery_GetLayoutIDs (LayoutName ; SkipLayoutNameCheck)
Optional Parameters	<p>LayoutName If you specify this parameter, CNS Query will return the ID of the Layout you specify. Otherwise, CNS Query will return all the IDs of all the Layouts.</p> <p>SkipLayoutNameCheck If True, CNS Query will not check to make sure the Layout Name you specify actually exists.</p>
Related Items	CNSQuery_GetLayoutFieldNames CNSQuery_GetLayoutNames CNSQuery_LayoutExists
Examples	<p>Example 1 Returns something like: ZLayout=1 YLayout=2</p> <pre>CNSQuery_GetLayoutIDs</pre> <hr/> <p>Example 2 Returns 2 if the Layout ID for the "YLayout" Layout in the current Database File is 2.</p> <pre>CNSQuery_GetLayoutIDs("YLayout")</pre>

CNSQuery_GetLayoutNames

Name	CNSQuery_GetLayoutNames
Description	This function returns a list of Layout Names from the current Database File.
Return Type	Text
Format	CNSQuery_GetLayoutNames
Related Items	CNSQuery_GetLayoutFieldNames CNSQuery_GetLayoutIDs CNSQuery_LayoutExists
Example	Example 1 Returns something like: ZLayout YLayout CNSQuery_GetLayoutNames

CNSQuery_GetTOIDs

Name	CNSQuery_GetTOIDs
Description	<p>This function returns either the ID of a specific Table Occurrence or a list of "TOName=TOID" pairs for all Table Occurrences in the Database File. If you specify a TO Name in the first parameter, CNS Query will return the Table Occurrence ID of that specific Table Occurrence. If you do not specify this parameter, CNS Query will return a list of "TOName=TOID" pairs for all the TOs in the Database File. By default, CNS Query will check to make sure the TO Name you specify exists before getting the Table ID. If you already know for sure that the TO Name exists, you can pass True as the second parameter.</p>
Return Type	Text or Number
Format	CNSQuery_GetTOIDs (TOName ; SkipTONameCheck)
Optional Parameters	<p>TOName If you specify this parameter, CNS Query will return the ID of the Table Occurrence you specify. Specify "" to return the Table Occurrence IDs of all Table Occurrences. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) followed by a period to retrieve all the Table Occurrence IDs in that file (eg. "FileName."). Also in FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specify actually exists.</p>
Related Items	CNSQuery_AddTable CNSQuery_GetTONames CNSQuery_RemoveTable CNSQuery_TOExists CNSQuery_GetBaseTableNames
Examples	<p>Example 1 Returns something like:
 MyTable=1065089
 AnotherTable=1065092</p> <p>CNSQuery_GetTOIDs</p>

Example 2

Returns 1065092 if the TO ID for the "AnotherTable" Table in the current Database File is 1065092.

```
CNSQuery_GetTOIDs( "AnotherTable" )
```

Example 3

In FileMaker Pro 11 and above, use this form to get all the Table Occurrence IDs from a separate, open Database file.

```
CNSQuery_GetTOIDs( "AnotherFile." )
```

Example 4

In FileMaker Pro 11 and above, use this form to get the Table Occurrence ID from a Table Occurrence in a separate, open Database file.

```
CNSQuery_GetTOIDs( "AnotherFile.MyTable" )
```

CNSQuery_GetTONames

Name	CNSQuery_GetTONames
Description	This function returns a list of Table Occurrence Names from the Database File. With FileMaker Pro 11, if the optional FileName parameter is defined, this function will return a list of the Table Occurrence Names from that Database File.
Return Type	Text
Format	CNSQuery_GetTONames (FileName)
Optional Parameters	<p>FileName If you specify this parameter, CNS Query will return the Table Occurrence Names from this Database File (if it is open).</p> <p>Note: This parameter is only available with FileMaker Pro 11 and above.</p>
Related Items	CNSQuery_AddTable CNSQuery_GetTOIDs CNSQuery_RemoveTable CNSQuery_TOExists CNSQuery_GetBaseTableNames
Examples	<p>Example 1 Returns something like:
 MyTable
 AnotherTable</p> <p>CNSQuery_GetTONames</p> <hr/> <p>Example 2 In FileMaker Pro 11 and above, use this form to get the Table Occurrence Names from a separate, open Database file.</p> <p>CNSQuery_GetTONames("AnotherFile")</p>

CNSQuery_LayoutExists

Name	CNSQuery_LayoutExists
Description	This function checks for the Existence of a Layout in the current Database File. The parameter is the Name of the Layout to look for.
Return Type	Number (1=True, 0=False)
Format	CNSQuery_LayoutExists (LayoutName)
Required Parameters	LayoutName The Name of the Layout to search for.
Related Items	CNSQuery_GetLayoutFieldNames CNSQuery_GetLayoutIDs CNSQuery_GetLayoutNames
Example	Example 1 Returns 1 when a Layout Named "ZLayout" exists in the current Database File. CNSQuery_LayoutExists("ZLayout")

CNSQuery_RemoveField

Name	CNSQuery_RemoveField
Description	<p>This function Removes a Field from a Table. The first parameter is the Name of a Table Occurrence of the Table to Remove the Field from. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout TO and Remove the Field from that TO. The second parameter is the Name of the Field to Remove. By default, CNS Query will check to make sure the TO Name and the Field Name you specify exist before attempting to Remove the Field. If you already know for sure that the TO Name and the Field Name exist, you can pass True as the third and fourth parameters.</p> <p>Note: In FileMaker Pro 8.5 and above, you must insert a "Pause" Script Step after using this function in order for the Field to be Removed.</p>
Return Type	Text
Format	CNSQuery_RemoveField (TOName ; FieldName ; SkipTONameCheck ; SkipFieldNameCheck)
Required Parameters	<p>TOName The Name of the Table Occurrence to Remove the Field from. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldName The Name of the Field to Remove.</p>
Optional Parameters	<p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specified actually exists before attempting to Remove the Field.</p> <p>SkipFieldNameCheck If True, CNS Query will not check to make sure the Field Name you specified actually exists before attempting to Remove the Field.</p>
Related Items	CNSQuery_AddField CNSQuery_FieldExists CNSQuery_GetFieldIDs CNSQuery_GetFieldTypes CNSQuery_GetFieldValueByFind CNSQuery_GetFieldValueByID

CNSQuery_SetFieldValueByFind
CNSQuery_SetFieldValueByID

Examples

Example 1

Removes the "MyField" Field from the "MyTable" Table.

```
CNSQuery_RemoveField( "MyTable" ; "MyField" )
```

Example 2

In FileMaker Pro 11 and above, use this form to Remove a Field from a Table in a separate, open Database file.

```
CNSQuery_RemoveField( "AnotherFile.MyTable" ; "MyField" )
```

CNSQuery_RemoveRecordByFind

Name	CNSQuery_RemoveRecordByFind
Description	<p>This function Removes one or more Records based on a Find Criteria. The first parameter is the Name of a Table Occurrence for the Table to Remove the Record from. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout TO to Remove the Record from. The second parameter is a return- or paragraph mark-separated list of "FieldName=FieldValue" pairs that describes the Criteria for Finding the Record or Records to Remove. See the "Finding What You Want" section in the CNSQuery_FindRecords function for help in defining your Find Criteria. By default, CNS Query will only Remove the first Record it finds. If you want to Remove all Records that match the Find Criteria, specify True as the third parameter. By default, CNS Query will check to make sure the TO Name and the Field Names you specify exist before attempting to Remove the Record. If you already know for sure that the TO Name and the Field Names exist, you can pass True as the fourth and fifth parameters. By default, CNS Query will double-check to make sure the Record or Records were actually removed. If you would rather the plug-in skip this step, specify True as the sixth parameter. Finally, if you want the Find to be Case Sensitive, you can specify True as the last parameter.</p>
Return Type	Text
Format	CNSQuery_RemoveRecordByFind (TOName ; FindCriteria ; RemoveAllMatches ; SkipTONameCheck ; SkipFieldNameChecks ; SkipConfirmRemoval ; CaseSensitive)
Required Parameters	<p>TOName The Name of the Table Occurrence that contains the Record you want to Remove. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FindCriteria A return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the Criteria for Finding the Record to Remove. See the "Finding What You Want" section of the CNSQuery_FindRecords function for help in setting up the Find Criteria.</p>
Optional Parameters	<p>RemoveAllMatches If True, CNS Query will Remove all Records that match the Find Criteria. Default is False.</p>

SkipTONameCheck

If True, CNS Query will not check to make sure the TO Name you specified actually exists before Removing the Record.

SkipFieldNameChecks

If True, CNS Query will not check to make sure the Field Names you specified actually exist before Removing the Record.

SkipConfirmRemoval

If True, CNS Query will not double-check to make sure the Record was Removed.

CaseSensitive

If True, CNS Query will preserve the Case in the Field Values of the Find Criteria. (In other words, if CaseSensitive is True, "Green" would not match "green".)

Related Items

CNSQuery_AddRecord
CNSQuery_FindRecords
CNSQuery_RemoveRecordByID
CNSQuery_UpdateRecordByFind
CNSQuery_UpdateRecordByID

Examples**Example 1**

This would Remove the first Record in the "MyTable" Table where the "AField" Field had the value "some value".

```
CNSQuery_RemoveRecordByFind( "MyTable" ; "AField=some value" )
```

Example 2

This would Remove all Records in the current Table where the Values of the "LastName" field started with a "J".

```
CNSQuery_RemoveRecordByFind( "" ; "::Begins-With::LastName=J" ; True )
```

Example 3

In FileMaker Pro 11 and above, use this form to Remove a Record from a Table Occurrence in a separate, open Database file.

```
CNSQuery_RemoveRecordByFind( "AnotherFile.MyTable" ; "AField=some value" )
```


CNSQuery_RemoveRecordByID

Name	CNSQuery_RemoveRecordByID
Description	<p>This function Removes a Record from a Table using its Internal FileMaker Record ID. The first parameter is the Name of a Table Occurrence of the Table to Remove the Record from. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout TO to Remove the Record from. The second parameter is the Internal FileMaker Record ID of the Record you want to Remove. By default, CNS Query will check to make sure the TO Name and the Record ID you specify actually exist before attempting to Remove the Record. If you already know for sure that the TO Name and the Record ID exist, you can pass True as the third and fourth parameters. By default, CNS Query will double-check to make sure the Record was actually Removed. If you would rather the plug-in skip this step, specify True as the fifth parameter.</p>
Return Type	Text
Format	CNSQuery_RemoveRecordByID (TOName ; FMRecID ; SkipTONameCheck ; SkipFMRecIDCheck ; SkipConfirmRemoval)
Required Parameters	<p>TOName The Name of the Table Occurrence that contains the Record you want to Remove. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FMRecID The Internal FileMaker Record ID of the Record to Remove.</p>
Optional Parameters	<p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specified actually exists before Removing the Record.</p> <p>SkipFMRecIDCheck If True, CNS Query will not check to make sure the Record ID you specified actually exists before Removing the Record.</p> <p>SkipConfirmRemoval If True, CNS Query will not double-check to make sure the Record was Removed.</p>
Related Items	CNSQuery_AddRecord

CNSQuery_FindRecords
CNSQuery_RemoveRecordByFind
CNSQuery_UpdateRecordByFind
CNSQuery_UpdateRecordByID

Examples

Example 1

This would Remove the Record with the Record ID 2 from the "MyTable" Table.

```
CNSQuery_RemoveRecordByID( "MyTable" ; 2 )
```

Example 2

In FileMaker Pro 11 and above, use this form to Remove a Record from a Table Occurrence in a separate, open Database file.

```
CNSQuery_RemoveRecordByID( "AnotherFile.MyTable" ; 4 )
```

CNSQuery_RemoveTable

Name	CNSQuery_RemoveTable
Description	This function Removes the Base Table corresponding to the Table Occurrence Name you specify. The first parameter is the Name of a Table Occurrence for the Table to Remove.
Return Type	Text
Format	CNSQuery_RemoveTable (TOName)
Required Parameters	TOName The Name of the Table Occurrence corresponding to the Base Table you want to Remove. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".
Related Items	CNSQuery_AddTable CNSQuery_GetTOIDs CNSQuery_GetTONames CNSQuery_TOExists CNSQuery_GetBaseTableNames
Examples	Example 1 Removes the "MyOldTable" Table from the current Database File. <pre>CNSQuery_RemoveTable("MyOldTable")</pre> <hr/> Example 2 In FileMaker Pro 11 and above, use this form to Remove a Base Table with the Table Occurrence specified in a separate, open Database file. <pre>CNSQuery_RemoveTable("AnotherFile.MyOldTable")</pre>

CNSQuery_SetFieldValueByFind

Name	CNSQuery_SetFieldValueByFind
Description	<p>This function Sets the Value of a single Field using Find Criteria. The first parameter is the Name of a Table Occurrence of the Table to Set the Field Value in. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout TO to Set the Field Value in. The second parameter is the Name of the Field to set. The third parameter is the new Value for the Field. The fourth parameter is a return- or paragraph mark-separated list of "FieldName=FieldValue" pairs that describes the Criteria for Finding the Record to Set the Field Value in. See the "Finding What You Want" section in the CNSQuery_FindRecords function for help in defining your Find Criteria. By default, CNS Query will check to make sure the TO Name and all the Field Names you specify exist before attempting to Set the Field Value. If you already know for sure that the TO Name and the Field Names exist, you can pass True as the fifth and sixth parameters. Finally, if you want the Find to be Case Sensitive, you can specify True as the last parameter.</p>
Return Type	Text
Format	CNSQuery_SetFieldValueByFind (TOName ; FieldName ; FieldValue ; FindCriteria ; SkipTONameCheck ; SkipFieldNameChecks ; CaseSensitive)
Required Parameters	<p>TOName The Name of the Table Occurrence to Set the Field Value in. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldName The Name of the Field to Set.</p> <p>FieldValue The new Value for the Field.</p> <p>FindCriteria A return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the Criteria for Finding the Record to Set the Field Value in. See the "Finding What You Want" section of the CNSQuery_FindRecords function for help in setting up the Find Criteria.</p>
Optional Parameters	SkipTONameCheck

If True, CNS Query will not check to make sure the TO Name you specified actually exists before Setting the Field Value.

SkipFieldNameChecks

If True, CNS Query will not check to make sure all the Field Names in the various parameters actually exist before Setting the Field Value.

CaseSensitive

If True, CNS Query will preserve the Case in the Field Values of the Find Criteria. (In other words, if CaseSensitive is True, "Green" would not match "green".)

Related Items

CNSQuery_AddField
CNSQuery_FieldExists
CNSQuery_FindRecords
CNSQuery_GetFieldIDs
CNSQuery_GetFieldNames
CNSQuery_GetFieldTypes
CNSQuery_GetFieldValueByFind
CNSQuery_GetFieldValueByID
CNSQuery_RemoveField
CNSQuery_SetFieldValueByID

Examples

Example 1

This would Set the Value of the "BField" Field to "A New Value" in the "MyTable" Table for the first Record where the "AField" Field has the Value "some value".

```
CNSQuery_SetFieldValueByFind( "MyTable" ; "BField" ; "A New Value" ; "AField=some value" )
```

Example 2

This would Set the Value of the "LastName" Field to "Jones" in the current Table for the first Record where the "FirstName" Field has the Value "Ann".

```
CNSQuery_SetFieldValueByFind( "" ; "LastName" ; "Jones" ; "FirstName=Ann" )
```

Example 3

In FileMaker Pro 11 and above, use this form to Set a Field Value in a Table Occurrence in a separate, open Database file.

```
CNSQuery_SetFieldValueByFind( "AnotherFile.MyTable" ; "BField" ; "A New Value" ; "AField=some value" )
```


CNSQuery_SetFieldValueByID

Name	CNSQuery_SetFieldValueByID
Description	<p>This function Sets the Value of a single Field in a Record with a specific ID. The first parameter is the Name of a Table Occurrence of the Table to Set The Field Value in. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout TO to Set the Field Value in. The second parameter is the Name of the Field to Set. The third parameter is the new Value for the Field. The fourth parameter is the Internal FileMaker Record ID of the Record to Set the Field Value in. If you do not specify this parameter, CNS Query will use Get(RecordID) to get the Record ID. By default, CNS Query will check to make sure the TO Name, the Field Name, and the Record ID you specify exist before attempting to Set the Field Value. If you already know for sure that the TO Name, the Field Name, and the Record ID exist, you can pass True as the fifth, sixth, and seventh parameters.</p>
Return Type	Text
Format	CNSQuery_SetFieldValueByID (TOName ; FieldName ; FieldValue ; FMRecID ; SkipTONameCheck ; SkipFieldNameCheck ; SkipFMRecIDCheck)
Required Parameters	<p>TOName The Name of a Table Occurrence of the Table to Set the Field Value in. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FieldName The Name of the Field to Set.</p> <p>FieldValue The new Value for the Field.</p>
Optional Parameters	<p>FMRecID The Internal FileMaker Record ID of the Record to Set the Field Value in.</p> <p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specified actually exists before Setting the Field Value.</p> <p>SkipFieldNameCheck If True, CNS Query will not check to make sure the Field Name you specified actually exists before Setting the Field Value.</p>

SkipFMRecIDCheck

If True, CNS Query will not check to make sure the Record ID you specified actually exists before Setting the Field Value.

Related Items

CNSQuery_AddField
CNSQuery_FieldExists
CNSQuery_GetFieldIDs
CNSQuery_GetFieldNames
CNSQuery_GetFieldTypes
CNSQuery_GetFieldValueByFind
CNSQuery_GetFieldValueByID
CNSQuery_RemoveField
CNSQuery_SetFieldValueByFind

Examples**Example 1**

This would Set the Value of the "AField" Field in the "MyTable" Table" with the Record with ID 4 to the Value "some new value".

```
CNSQuery_SetFieldValueByID( "MyTable" ; "AField" ; "some new value" ; 4 )
```

Example 2

This would Set the Value of the "FirstName" Field of the current Record in the current Table to the Value "Maryanne".

```
CNSQuery_SetFieldValueByID( "" ; "FirstName" ; "Maryanne" )
```

Example 3

In FileMaker Pro 11 and above, use this form to Set a Field Value in a Table in a separate, open Database file.

```
CNSQuery_SetFieldValueByID( "AnotherFile.MyTable" ; "AField" ; "some new value" ; 4 )
```

CNSQuery_TOExists	
Name	CNSQuery_TOExists
Description	This function checks for the Existence of a Table Occurrence in the current Database File. The parameter is the Name of the Table Occurrence to look for.
Return Type	Number (1=True, 0=False)
Format	CNSQuery_TOExists (TOName)
Required Parameters	<p>TOName</p> <p>The Name of the Table Occurrence to search for. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p>
Related Items	<p>CNSQuery_AddTable</p> <p>CNSQuery_GetTOIDs</p> <p>CNSQuery_GetTONames</p> <p>CNSQuery_RemoveTable</p> <p>CNSQuery_GetBaseTableNames</p>
Examples	<p>Example 1</p> <p>Returns 1 when a Table Named "MyTable" exists in the current Database File.</p> <pre>CNSQuery_TableExists("MyTable")</pre> <hr/> <p>Example 2</p> <p>In FileMaker Pro 11 and above, use this form to check for a Table Occurrence in a separate, open Database file.</p> <pre>CNSQuery_TOExists("AnotherFile.MyTable")</pre>

CNSQuery_UpdateRecordByFind

Name	CNSQuery_UpdateRecordByFind
Description	<p>This function Updates one or more Records based on Find Criteria. The first parameter is the Name of a Table Occurrence of the Table to Update the Record in. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout TO to Update the Record in. The second parameter is a return- or paragraph mark-separated list of "FieldName="FieldValue" pairs describing the Criteria for Finding the Record or Records to Update. See the "Finding What You Want" section of the CNSQuery_FindRecords function for help in defining your Find Criteria. The third parameter is a return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the Field Values to Update the Record with. If a Field Value needs a return in it, you can use "<CR>" to indicate a return. By default, CNS Query will only Update the first Record it finds. If you want to Update all Records that match the Find Criteria, specify True as the fourth parameter. By default, CNS Query will check to make sure the TO Name and all the Field Names exist before attempting to Update the Record. If you already know for sure that the TO Name and the Field Names exist, you can pass True as the fifth and sixth parameters. Finally, if you want the Find to be Case Sensitive, you can specify True as the last parameter.</p>
Return Type	Text
Format	CNSQuery_UpdateRecordByFind (TOName ; FindCriteria ; FieldValues ; UpdateAllMatches ; SkipTONameCheck ; SkipFieldNameChecks ; CaseSensitive)
Required Parameters	<p>TOName The Name of a Table Occurrence of the Table that contains the Record you want to Update. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FindCriteria A return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the Criteria for Finding the Record to Update. See the "Finding What You Want" section of the CNSQuery_FindRecords function for help in setting up the Find Criteria.</p> <p>FieldValues A return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the new Field Values to Update the Record with. Use "<CR>" to indicate a return or new line in a Field Value.</p>

<p>Optional Parameters</p>	<p>UpdateAllMatches If True, CNS Query will Update all Records that match the Find Criteria. Default is False.</p> <p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specified actually exists before Updating the Record.</p> <p>SkipFieldNameChecks If True, CNS Query will not check to make sure all the Field Names you specified in the various parameters actually exist before Updating the Record.</p> <p>CaseSensitive If True, CNS Query will preserve the Case in the Field Values of the Find Criteria. (In other words, if CaseSensitive is True, "Green" would not match "green".)</p>
<p>Related Items</p>	<p>CNSQuery_AddRecord CNSQuery_FindRecords CNSQuery_RemoveRecordByFind CNSQuery_RemoveRecordByID CNSQuery_UpdateRecordByID</p>
<p>Examples</p>	<p>Example 1 Updates the first Record in the "MyTable" Table where the "AField" Field has the Value "some value", setting the "BField" Field to "some new value" and the "CField" Field to "some other value".</p> <pre>CNSQuery_UpdateRecordByFind("MyTable" ; "AField=some value" ; "BField=some new value¶CField=some other value")</pre> <hr/> <p>Example 2 Updates all Records in the current Table where the "State" Field has the value "Texas", setting the "Region" Field to the Value "South".</p> <pre>CNSQuery_UpdateRecordByFind("" ; "State=Texas" ; "Region=South" ; True)</pre> <hr/> <p>Example 3 In FileMaker Pro 11 and above, use this form to Update a Record in a Table Occurrence in a separate, open Database file.</p>

```
CNSQuery_UpdateRecordByFind( "AnotherFile.MyTable" ;  
"AField=some value" ; "BField=some new vlaue")
```

CNSQuery_UpdateRecordByID

Name	CNSQuery_UpdateRecordByID
Description	<p>This function Updates a Record in a Table Occurrence using its Internal FileMaker Record ID. The first parameter is the Name of a Table Occurrence of the Table to Update the Record in. If you do not specify this parameter, CNS Query will use Get(LayoutTableName) to get the Current Layout Table to Update the Record in. The second parameter is the Internal FileMaker Record ID of the Record you want to Update. The third parameter is a return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the Field Values to Update the Record with. If a Field Value needs a return in it, you can use "<CR>" to indicate a return. By default, CNS Query will check to make sure the TO Name, the Record ID, and the Field Names you specify exist before attempting to Update the Record. If you already know for sure that the TO Name, the Record ID, and the Field Names exist, you can pass True as the fourth, fifth, and sixth parameters.</p>
Return Type	Text
Format	CNSQuery_UpdateRecordByID (TOName ; FMRecID ; FieldValues ; SkipTONameCheck ; SkipFMRecIDCheck ; SkipFieldNameChecks)
Required Parameters	<p>TOName The Name of the Table Occurrence that contains the Record you want to Update. Specify "" to use the Current Layout TO. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>FMRecID The Internal FileMaker Record ID of the Record to Update.</p> <p>FieldValues A return- or paragraph mark-separated list of "FieldName=FieldValue" pairs describing the new Field Values to Update the Record with. Use "<CR>" to indicate a return or new line in a Field Value.</p>
Optional Parameters	<p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specified actually exists before Updating the Record.</p> <p>SkipFMRecIDCheck If True, CNS Query will not check to make sure the Record ID you specified actually exists before Updating the Record.</p> <p>SkipFieldNameChecks</p>

If True, CNS Query will not check to make sure the Field Names you specified actually exist before Updating the Record.

Related Items

CNSQuery_AddRecord
CNSQuery_FindRecords
CNSQuery_RemoveRecordByFind
CNSQuery_RemoveRecordByID
CNSQuery_UpdateRecordByFind

Examples

Example 1

Updates the Record with the ID 2 in the "MyTable" Table, setting the "BField" Field to "some new value" and the "CField" Field to "some other value".

```
CNSQuery_UpdateRecordByID( "MyTable" ; 2 ; "BField=some new value¶CField=some other value" )
```

Example 2

Updates the Record with ID 4 in the current Table, setting the "Description" field with a multi-line value.

```
CNSQuery_UpdateRecordByID( "" ; 4 ;  
"Description=some<CR>value<CR>with<CR>multiple<CR>lines" )
```

Example 3

In FileMaker Pro 11 and above, use this form to Update a Record in a Table Occurrence in a separate, open Database file.

```
CNSQuery_UpdateRecordByID( "AnotherFile.MyTable" ; 4 ;  
"BField=some new value" )
```

CNSQuery_Version	
Name	CNSQuery_Version
Description	This function returns the current version of CNS Query. This function is useful for testing whether or not the plug-in is installed and enabled. If you call this function and a question mark ("?") is returned, then the plug-in is either not installed or not enabled.
Return Type	Text
Format	CNSQuery_Version
Related Items	CNSQuery_VersionAutoUpdate
Example	Example 1 Returns the CNS Query version like "CNS Query v.1.1.1". CNSQuery_Version

CNSQuery_Register

Name	CNSQuery_Register
Description	You can use this function to Register the plug-in from a script instead of through the Configuration Dialog. This is useful when the plug-in is being distributed to many computers, allowing you to install and register the plug-in without having to physically visit each computer. This function also allows you to check if the plug-in is already registered or clear the current registration. The plug-in always requires you to accept the License Agreement to use the plug-in. This is usually done by presenting the License Agreement Dialog, but that can be suppressed by using the special option value "I Accept the License Agreement".
Return Type	Text
Format	CNSQuery_Register (FirstName ; LastName ; LicenseKey ; Option)
Required Parameters	FirstName The Registration First Name you specified when you ordered. (See your Receipt.) LastName The Registration Last Name you specified when you ordered. (See your Receipt.) LicenseKey The License Key from your Receipt.
Optional Parameters	Option Specify "Dialog" to enter your Registration Information in a dialog. Specify "Check" to see if the plug-in is already Registered. Specify "Clear" to remove the Registration. Specify "I Accept the License Agreement" to automatically accept the License Agreement dialog without showing it to the end user. Notes: The "Dialog", "Check", and "Clear" options can also be specified as the first parameter. If you have a Developer License, do not use the "I Accept the License Agreement" value here. See your Developer Instructions file for more information.
Examples	Example 1 Registers the plug-in with the provided registration information (obviously the above is not valid registration information; please see your Receipt). CNSQuery_Register("My First Name" ; "My Last Name" ; "My License Key")

Example 2

Displays a dialog for you to enter your First Name, Last Name, and Registration Number as it appears on your Receipt.

```
CNSQuery_Register( "Dialog" )
```

Example 3

Returns "Not Registered." or "Registered to <name> for a <license>."

```
CNSQuery_Register( "Check" )
```

Example 4

Registers the plug-in and uses the "I Accept the License Agreement" option to keep the License Agreement dialog from appearing.

```
CNSQuery_Register( "My Company Name" ; "My Company Name" ;  
"My Site License Number" ; "I Accept the License Agreement" )
```

CNSQuery_Configure	
Name	CNSQuery_Configure
Description	<p>Calling this function with no parameters will open the CNS Query Configuration Dialog. You can optionally open to a specific tab by specifying the name of the tab as the "Option" parameter. This function also allows you to get or set any preference found in the Configuration Dialog.</p> <p>Valid PrefNames:</p> <p>"AddHelp" - If True, Function specific Help will be added to Calculations when inserting the Plug-in's Functions.</p> <p>"AlwaysUseFileSQL" - If True, and if running under FileMaker Pro 11+, the plug-in will always use the newer, more strict/more complete, SQL Interface.</p>
Return Type	Varies
Format	CNSQuery_Configure (Option ; PrefName ; PrefValue)
Optional Parameters	<p>Option Specify the name of a Tab in the Configuration Dialog to show it opened to that tab.</p> <p>Specify "Get" with the PrefName parameter to get a preference value. (If not found, and PrefValue is defined, PrefValue will be returned.)</p> <p>Specify "Set" with the PrefName and PrefValue parameters to set a preference value.</p> <p>PrefName The Name of the Preference to Get or Set. (See the Function Description for a list of valid PrefNames.)</p> <p>PrefValue The Value of the Preference to Set. (See the Function Description for some possible values.)</p>
Examples	<p>Example 1 Opens the CNS Query Configuration Dialog. (Because the "Option" parameter is not used, the dialog will open to the "Basics" tab.)</p> <p>CNSQuery_Configure</p> <hr/> <p>Example 2 Opens the CNS Query Configuration Dialog to the "About" tab.</p>

```
CNSQuery_Configure( "About" )
```

Example 3

Returns the value of the 'Add Help Comments to External Functions' setting from the Configuration Dialog.

```
CNSQuery_Configure( "Get" ; "AddHelp" )
```

Example 4

Sets the 'Always use new SQL Interface' setting in the Configuration Dialog to true.

```
CNSQuery_Configure( "Set" ; "AlwaysUseFileSQL" ; "True" )
```

CNSQuery_VersionAutoUpdate

Name	CNSQuery_VersionAutoUpdate
Description	<p>This function returns an Auto Update friendly Version number of CNS Query. The format of this version number is always exactly 8 digits long. The first two digits represent the major version of the plug-in (zero-filled). The third and fourth digits represent the minor version of the plug-in (zero-filled). The fifth and sixth digits represent the update portion of the version (zero-filled). The final two digits represent a special build number or a beta version number and will usually be zeros.</p> <p>As an example, for CNS Query 1.1.1, the major version is 1, the minor version is 1, the update number is 1, and there is no special build or beta version defined. So, the resulting Auto Update friendly version number would be 01010100.</p>
Return Type	Number
Format	CNSQuery_VersionAutoUpdate
Related Items	CNSQuery_Version
Example	<p>Example 1 Returns 01010100 for CNS Query version 1.1.1.</p> <p>CNSQuery_VersionAutoUpdate</p>

CNSQuery_ExecuteSQLEx

Name	CNSQuery_ExecuteSQLEx
Description	<p>Note: This function is only available in FileMaker Pro 11 and above.</p> <p>This "extended" version of CNSQuery_ExecuteSQL allows you to optionally specify a separate, open Database File from the current Database File. The third parameter allows you to specify that the plug-in store the results internally, which you can then retrieve the value from individual cells using the CNSQuery_GetRecordData function. Retrieving the data in this manner allows you to retrieve not just textual values, but any of the FileMaker Pro Data Types including Container data. On the other hand, if you want the results returned as text, you can optionally define the Separators that should be placed between the Fields and Records using the last two parameters. By default, CNS Query will use a comma between multiple Fields and a return between multiple Records. The Field and Record Separators you specify are not limited to a single character. Finally, this function allows you to use "SQL Parameters" (question marks in your query) and then specify those parameters starting with the sixth parameter position. This allows you to create queries that can copy Stored Container data into other fields, among other things.</p>
Return Type	Text
Format	CNSQuery_ExecuteSQLEx (FileName ; SQL ; UseRecordData ; FieldSeparator ; RecordSeparator ; ...)
Required Parameters	<p>FileName The FileName (without the extension) of the open Database File you are wanting to run this SQL query against. Specify "" to use the Current File.</p> <p>SQL The SQL statement to evaluate.</p>
Optional Parameters	<p>UseRecordData If True, this function will return a blank response when successful and you can use the CNSQuery_GetRecordData function to retrieve any data. By default, this is False.</p> <p>FieldSeparator The Separator to use between multiple Fields when doing an SQL Select. By default, Fields will be separated with a comma.</p> <p>RecordSeparator</p>

The Separator to use between multiple Records when doing an SQL Select. By default, Records will be separated with a return.

...

Any number of extra parameters corresponding to any '?'s in your SQL query.

Related Items

CNSQuery_EscapeQuotes
CNSQuery_ExecuteSQL
CNSQuery_GetAsSQLDate
CNSQuery_GetAsSQLTime
CNSQuery_GetAsSQLTimestamp
CNSQuery_GetRecordData
CNSQuery_GetRecordDataColumnCount
CNSQuery_GetRecordDataRowCount

Examples

Example 1

Returns an empty response (meaning success), and populates the internal Record Data with every field and every record from the "MyTable" Table Occurrence in the current Database File.

```
CNSQuery_ExecuteSQLEx( "" ; "select * from MyTable" ; True )
```

Example 2

Returns something like "<tr><td>Mary</td><td>Jones</td></tr>" for every record in the "People" Table Occurrence in the "Contacts" Database File.

```
CNSQuery_ExecuteSQLEx( "Contacts" ; "select '<tr><td>' +  
\\"First\\", \\"Last\\" + '</td></tr>' from People" ; False ; "  
</td><td>" )
```

Example 3

Sets the "Photo" field in the "People" TO with the value from the "SomeContainerField" field.

```
CNSQuery_ExecuteSQLEx( "" ; "update People set \\"Photo\\"=?" ;  
False ; "," ; "¶" ; SomeContainerField )
```

CNSQuery_GetAsSQLDate

Name	CNSQuery_GetAsSQLDate
Description	This function will convert a FileMaker Pro Date value into an SQL Date Format suitable for using in an SQL query.
Return Type	Text
Format	CNSQuery_GetAsSQLDate (FMPDate)
Required Parameters	FMPDate The FileMaker Pro Date to convert to an SQL formatted Date.
Related Items	CNSQuery_GetAsSQLTime CNSQuery_GetAsSQLTimestamp
Example	Example 1 Returns something like: 2010-03-29 CNSQuery_GetAsSQLDate(MyDate)

CNSQuery_GetAsSQLTime

Name	CNSQuery_GetAsSQLTime
Description	This function will convert a FileMaker Pro Time value into an SQL Time Format suitable for using in an SQL query.
Return Type	Text
Format	CNSQuery_GetAsSQLTime (FMPTime)
Required Parameters	FMPTime The FileMaker Pro Time to convert to an SQL formatted Time.
Related Items	CNSQuery_GetAsSQLDate CNSQuery_GetAsSQLTimestamp
Example	Example 1 Returns something like: 14:47:43 CNSQuery_GetAsSQLTime(MyTime)

CNSQuery_GetAsSQLTimestamp

Name	CNSQuery_GetAsSQLTimestamp
Description	This function will convert a FileMaker Pro Timestamp value into an SQL Timestamp Format suitable for using in an SQL query.
Return Type	Text
Format	CNSQuery_GetAsSQLTimestamp (FMPTimestamp)
Required Parameters	FMPTimestamp The FileMaker Pro Timestamp to convert to an SQL formatted Timestamp.
Related Items	CNSQuery_GetAsSQLDate CNSQuery_GetAsSQLTime
Example	Example 1 Returns something like: 2010-03-29 14:48:56 CNSQuery_GetAsSQLTimestamp(MyTimestamp)

CNSQuery_GetBaseTableNames

Name	CNSQuery_GetBaseTableNames
Description	<p>Note: This function is only available in FileMaker Pro 11 and above.</p> <p>This function returns either the Base Table Name of a specific Table Occurrence or a list of "TOName=BaseTableName" pairs for all Table Occurrences in a Database. If you specify a TOName as the first parameter, it will return the Base Table Name of that Table Occurrence, otherwise it will return all Base Table Names. By default, CNS Query will check to make sure the Table Occurrence Name you specify exists before getting the Base Table Names. If you already know for sure that the TO Name exists, you can pass True as the second parameter.</p>
Return Type	Text
Format	CNSQuery_GetBaseTableNames (TOName ; SkipTONameCheck)
Optional Parameters	<p>TOName If you only want the Base Table Name of one Table Occurrence, specify its Name here. Specify "" to return the Base Table Names of all Table Occurrences. In FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) followed by a period to retrieve all the Base Table Names in that file (eg. "FileName."). Also in FileMaker Pro 11 and above, you can optionally specify the Database Filename (without the ".fp7" extension) containing the TO in the format "FileName.TOName".</p> <p>SkipTONameCheck If True, CNS Query will not check to make sure the TO Name you specify actually exists.</p>
Related Items	CNSQuery_GetTOIDs CNSQuery_GetTONames CNSQuery_TOExists
Examples	<p>Example 1 Returns something like:
 Students=People
 Teachers=People</p> <p>CNSQuery_GetBaseTableNames</p> <hr/>

Example 2

In FileMaker Pro 11 and above, use this form to get the Base Table Names of all Table Occurrences in a separate, open Database file.

```
CNSQuery_GetFieldIDs( "AnotherFile." )
```

Example 3

In FileMaker Pro 11 and above, use this form to get the Base Table Name of a Table Occurrence in a separate, open Database file.

```
CNSQuery_GetFieldIDs( "AnotherFile.MyTable" )
```

CNSQuery_GetRecordData

Name	CNSQuery_GetRecordData
Description	<p>Note: This function is only available in FileMaker Pro 11 and above.</p> <p>When using the new CNSQuery_ExecuteSQLEx function or the modified CNSQuery_FindRecords function, you can optionally specify that the results be stored internally in the plug-in. This function is used to retrieve those results. The first parameter is the Row or Record number of the result to look in. The second parameter is the Column or Field number of the result to look in.</p>
Return Type	Varies
Format	CNSQuery_GetRecordData (Row ; Column)
Required Parameters	<p>Row The Row of Record Data to return. Note: The first Row is at position 0 (zero).</p> <p>Column The Column of Record Data to return. Note: The first Column is at position 0 (zero).</p>
Related Items	CNSQuery_ExecuteSQLEx CNSQuery_FindRecords CNSQuery_GetRecordDataColumnCount CNSQuery_GetRecordDataRowCount
Example	<p>Example 1 Returns the value of the field in the first record of results in the 4th field.</p> <pre>CNSQuery_GetRecordData(0 ; 4)</pre>

CNSQuery_GetRecordDataColumnCount

Name	CNSQuery_GetRecordDataColumnCount
Description	<p>Note: This function is only available in FileMaker Pro 11 and above.</p> <p>This function returns the number of Columns or Fields in the current stored Record Data.</p>
Return Type	Number
Format	CNSQuery_GetRecordDataColumnCount
Related Items	CNSQuery_GetRecordData CNSQuery_GetRecordDataRowCount
Example	<p>Example 1</p> <p>This would return 4 if the current stored Record Data had 4 columns of data.</p> <p>CNSQuery_GetRecordDataColumnCount</p>

CNSQuery_GetRecordDataRowCount

Name	CNSQuery_GetRecordDataRowCount
Description	<p>Note: This function is only available in FileMaker Pro 11 and above.</p> <p>This function returns the number of Rows or Records in the current stored Record Data.</p>
Return Type	Number
Format	CNSQuery_GetRecordDataRowCount
Related Items	CNSQuery_GetRecord CNSQuery_GetRecordDataColumnCount
Example	<p>Example 1</p> <p>This would return 10 if the current stored Record Data had 10 rows of data.</p> <p>CNSQuery_GetRecordDataRowCount</p>